

## BARCODE READER

# LASER SCANNER WITH STAND PS2 INTERFACE

## BL-2000K

\* 5,900.-

(C-YA-A-00083)



### Specifications

General	
Interface	Keyboard Wedge PS2
Supported Symbolologies	UPC-A/UPC-E, EA N-13, Codabar, Code 11, Code 39, Code 93, Code 32, Code 128, Telepen Code, RSS Code Industril 2 of 5, Interleaved 2 of 5, MSI Plessey Code, EAN/UCC 128, IATA Code, China Postal Code
Optical	
Optical sensors	Photo diode
Width of Field	120 mm
Light source	Laser diode (650 nm)
Depth of Field	30 ~ 250 mm (UPC/EAN PCS=90%)
Resolution	0.1 mm (PCS=90%)
Ambient Light	3000 Lux/Max (Fluorescent Light)
Scanning contrast gradient	=> 45%
Scanning angle	36° ± 2°
Electrical	
Power Supply Voltage	5VDC ± 5%
Working currents	135 mA
Standby currents	65 mA
Readind indicator	Beeper and Led
Scan Rate	90 scan/sec
Environment	
Temperature in operation	0° C ~ 50° C
Temperature in storage	-20° C ~ +60° C
Humidity in operation	20%RH ~85%RH
Humidity in storage	10%rh ~ 90%RH
Safety Approval	CE, FCC Class B, RoHS Approved
Physical	
Housing Material	ABS plastic
Cable length	1.5 M
Connector	RJ45 Phone jack connector 10 pins
Weight scanner	220 g ± 5 g (with Cable)
Dimensions	160 mm (L) x 70 mm (W) x 80 mm (H)
Shock resistance	Approved by 1.5M drop test onto concrete ground